



TECHNICAL DATA SHEET

SENSHI 0W-16 FULLY SYNTHETIC

MEETS PERFORMANCE STANDARD:
API SQ/RC, ILSAC GF-7B

DESCRIPTION:

0W-16 is a fully synthetic, ultra-low viscosity engine oil developed for modern vehicles designed with fuel efficiency in mind. Its advanced formula helps reduce internal friction to support improved fuel economy while providing reliable protection against engine wear.

Designed for fast oil circulation during cold starts, 0W-16 delivers quick lubrication to critical engine components and maintains strong stability under high operating temperatures. This helps promote smooth engine performance, dependable protection, and long-term engine durability.

KEY FEATURES:

- ✓ Advanced Wear Protection
- ✓ Enhanced Fuel Efficiency
- ✓ High Thermal Stability
- ✓ Smooth Engine Operation
- ✓ Cleaner Engine Performance



PARAMETER	METHOD	UNIT	TYPICAL RESULT
Viscosity Grade	SAE J300	-	0W-16
Color	VISUAL	-	Gold brown
Density @ 15°C	ASTM D4052	kg/m3	838.3
Kinematic Viscosity @ 40°C	ASTM D7042	mm ² /s	20.14
Kinematic Viscosity @ 100°C	ASTM D7042	mm ² /s	4.8405
Viscosity Index	ASTM D2270	-	174.23
Flash Point, °C	IP 523	°C	170
Pour Point, °C	ASTM D97	°C	-40

The information provided is believed to be accurate at the time of publication and may change without notice due to ongoing product development. Recommendations are given as general guidance only, and the manufacturer accepts no liability for loss or damage arising from its use.