



TECHNICAL DATA SHEET

SENSHI 0W-20 FULLY SYNTHETIC

MEETS PERFORMANCE STANDARD:

API SQ/RC, ILSAC GF-7A

DESCRIPTION:

0W-20 Fully Synthetic Engine Oil is formulated for modern petrol engines requiring a low-viscosity lubricant that supports efficient performance and dependable protection. Its advanced synthetic formulation helps reduce friction, protect critical engine components from wear, and promote smooth, responsive operation during everyday driving.

Designed for excellent cold-start flow and reliable high-temperature stability, Senshi 0W-20 helps deliver rapid lubrication when the engine starts while maintaining a strong protective film under heat and load. This supports improved fuel efficiency, cleaner engine operation, and long-term engine durability.

KEY FEATURES:

- ✓ Advanced Wear Protection
- ✓ Enhanced Fuel Efficiency
- ✓ High Thermal Stability
- ✓ Smooth Engine Operation
- ✓ Cleaner Engine Performance



PARAMETER	METHOD	UNIT	TYPICAL RESULT
Viscosity Grade	SAE J300	-	0W-20
Color	VISUAL	-	Gold brown
Density @ 15°C	ASTM D4052	kg/m3	849.8
Kinematic Viscosity @ 40°C	ASTM D7042	mm ² /s	45.286
Kinematic Viscosity @ 100°C	ASTM D7042	mm ² /s	7.8474
Viscosity Index	ASTM D2270	-	153.11
Flash Point, °C	IP 523	°C	220
Pour Point, °C	ASTM D97	°C	-37

The information provided is believed to be accurate at the time of publication and may change without notice due to ongoing product development. Recommendations are given as general guidance only, and the manufacturer accepts no liability for loss or damage arising from its use.