



TECHNICAL DATA SHEET

SENSHI 5W-20 FULLY SYNTHETIC

MEETS PERFORMANCE STANDARD:

API SQ/RC, ILSAC GF-7A

DESCRIPTION:

5W-20 Fully Synthetic Engine Oil is formulated for modern petrol engines requiring efficient lubrication, smooth performance, and dependable protection across a wide range of driving conditions. Its advanced synthetic formulation helps reduce internal friction, protect critical engine components from wear, and support responsive engine operation.

Designed for quick oil circulation during cold starts and stable performance at higher temperatures, 5W-20 provides reliable lubrication under everyday driving and extended operation. This helps support improved fuel efficiency, cleaner engine performance, and long-term engine durability.

KEY FEATURES:

- ✓ Advanced Wear Protection
- ✓ Enhanced Fuel Efficiency
- ✓ High Thermal Stability
- ✓ Smooth Engine Operation
- ✓ Cleaner Engine Performance



PARAMETER	METHOD	UNIT	TYPICAL RESULT
Viscosity Grade	SAE J300	-	5W-20
Color	VISUAL	-	Gold brown
Density @ 15°C	ASTM D4052	kg/m3	842.8
Kinematic Viscosity @ 40°C	ASTM D7042	mm ² /s	30.549
Kinematic Viscosity @ 100°C	ASTM D7042	mm ² /s	7.6275
Viscosity Index	ASTM D2270	-	169.54
Flash Point, °C	IP 523	°C	-40
Pour Point, °C	ASTM D97	°C	190

The information provided is believed to be accurate at the time of publication and may change without notice due to ongoing product development. Recommendations are given as general guidance only, and the manufacturer accepts no liability for loss or damage arising from its use.