



TECHNICAL DATA SHEET

SENSHI 5W-30 FULLY SYNTHETIC

MEETS PERFORMANCE STANDARD:

AP SQ/CF, ILSAC GF-7A

DESCRIPTION:

5W-30 Fully Synthetic Engine Oil is formulated to deliver dependable protection, smooth performance, and efficient lubrication for modern petrol engines. Its advanced synthetic formulation helps reduce friction, protect critical engine components from wear, and maintain consistent engine performance across everyday driving conditions.

Designed for reliable cold-start lubrication and strong high-temperature stability, 5W-30 helps maintain an effective protective oil film under varying loads and operating temperatures. This supports cleaner engine operation, smoother performance, and long-term engine durability.

KEY FEATURES:

- ✓ Advanced Wear Protection
- ✓ Enhanced Fuel Efficiency
- ✓ High Thermal Stability
- ✓ Smooth Engine Operation
- ✓ Cleaner Engine Performance



PARAMETER	METHOD	UNIT	TYPICAL RESULT
Viscosity Grade	SAE J300	-	5W-30
Color	VISUAL	-	Gold brown
Density @ 15°C	ASTM D4052	kg/m ³	853.7
Kinematic Viscosity @ 40°C	ASTM D7042	mm ² /s	63.83
Kinematic Viscosity @ 100°C	ASTM D7042	mm ² /s	10.739
Viscosity Index	ASTM D2270	-	159.28
Flash Point, °C	IP 523	°C	220
Pour Point, °C	ASTM D97	°C	-26

The information provided is believed to be accurate at the time of publication and may change without notice due to ongoing product development. Recommendations are given as general guidance only, and the manufacturer accepts no liability for loss or damage arising from its use.