



TECHNICAL DATA SHEET

SENSHI HD-70

MEETS PERFORMANCE STANDARD:

API CI-4/SL

DESCRIPTION:

SENSHI HD 70 is a heavy-duty monograde engine oil formulated to deliver dependable lubrication and engine protection under demanding operating conditions. Its robust formulation helps reduce friction and wear while maintaining a strong protective oil film at high operating temperatures.

Designed for engines requiring HD 70 viscosity, it supports smoother operation, helps control deposits, and provides consistent performance during prolonged use. SENSHI HD 70 is suitable for heavy-duty applications where reliable protection, durability, and stable lubrication are essential.

KEY FEATURES:

- ✓ Heavy Duty Engine Protection
- ✓ Strong High-Thermal Stability
- ✓ Reduces Engine Wear
- ✓ Reliable Lubrication Under Heavy Load



PARAMETER	METHOD	UNIT	TYPICAL RESULT
Viscosity Grade	-	-	HD 70
Color	VISUAL	-	Gold brown
Density @ 15°C	ASTM D4052	kg/m3	883.5
Kinematic Viscosity @ 40°C	ASTM D7042	mm ² /s	284.31
Kinematic Viscosity @ 100°C	ASTM D7042	mm ² /s	34.665
Total Base Number (TBN)	ASTM D2896	mg KOH/g	11
Viscosity Index	ASTM D2270	-	140.92
Flash Point, °C	IP 523	°C	240
Pour Point, °C	ASTM D97	°C	-11

The information provided is believed to be accurate at the time of publication and may change without notice due to ongoing product development. Recommendations are given as general guidance only, and the manufacturer accepts no liability for loss or damage arising from its use.